

MONTHLY ENVIRONMENTAL REPORT

March 2021

Name of Operation	Endeavor Mine
Name of Licensee	Endeavor Operations Pty Ltd
Environmental Protection Licence	No: 1301
Reporting Period Start Date	1 March 2021
Reporting End Date	31 March 2021

TABLE OF CONTENTS

1	INT	INTRODUCTION						
2		IITORING RESULTS						
	2.1	Dust Monitoring	3					
	2.1.1	Dust Monitoring Methodology and Limits	4					
	2.1.2	Monitoring Locations	4					
	2.1.3	Dust Monitoring Data	5					
	2.2	Groundwater Monitoring	5					
	2.2.2	Monitoring Locations	6					
	2.2.2	Monitoring Results Data	8					
	2.3	Tailings Deposition	10					
	2.3.2	Tailings Deposition: Data and Discussion	10					
3	RES	JLTS LOG	10					
4	COM	PLAINTS HOTLINE	10					

FIGURES LIST

Figure 2.1	Dust monitoring gauge located in the project	3
Figure 2.2	Endeavor Mine Dust Monitoring Locations	5
Figure 2.3	Location of the Piezometer Monitoring Locations	3

TABLES LIST

Table 2-1	Endeavor Mine Air Monitoring Requirements	.4
Table 2-2	Dust monitoring results March 2021	. 5
Table 2-3	EPA Monitoring Stations	.6
Table 2-4	EPA Monitoring Parameters	.7
Table 2-5	Groundwater monitoring results March 2021	.9
Table 2-6	Tailings Deposition for March 2021	10
Table 3-1	Laboratory results log	10

1 INTRODUCTION

We at Endeavor Mine conduct systematic and periodic environmental monitoring of our operations to substantiate the effectiveness of our environmental controls which are in place to protect the environment, the health of our workers, our neighbours and the greater community. The results in this report correspond to the **December 2020**. This report publishes the summary of the environmental monitoring carried during this month for dust deposition, tailings deposition and groundwater. All monitoring is conducted in accordance with regulatory requirements and the EOPL Annual Environmental Monitoring Plan. Samples are collected and handled in accordance and compliance with regulatory requirements and taken to laboratories accredited by the National Association of Testing Authorities (NATA) for analysis. The current report only presents the results for the groundwater monitoring campaign of December 2020, the results for dust deposition will be added once they are received from the laboratory.

2 MONITORING RESULTS

2.1 Dust Monitoring

Air quality aspects and impacts associated with site operations are managed in accordance with the Air Quality Management Plan (END-PLN-ENV-006) and the requirement detailed in NSW Environmental Protection Licence 1301.

The Endeavor Mine is located 47 km from the nearest town (Cobar) and 4.5 km away for its nearest sensitive receptor (residential property). Therefore, dust deposition at these potential receptors is considered a low environmental risk.

Nevertheless, dust deposition on and beyond the boundary of the lease has the potential to cause environmental harm. Therefore Endeavor Mine manages airborne contaminants on site through the use of water sprays and a water trucks with depositional dust monitoring stations strategically located along the boundary of ML158/159/160/161 to measure performance.



Figure 2.1 Dust monitoring gauge located in the project

2.1.1 Dust Monitoring Methodology and Limits

The Endeavor Mine Dust Monitoring Program measures dust deposition rates on a monthly basis at the main mining lease boundary (4 locations) and at a background location located 11km from the operating mine site (DDG 5 – Point ID 5). EP Licence 1301 does not set limits for dust deposition. However, these results are compared to the recommended limits outlined in *Approved Methods for the Modelling and Assessment of Air Pollutants in NSW 2016*. This guidance document recommends that the deposition rate for total insoluble matter when expressed as a 12 month rolling average should not exceed 4 g/m²/month and that site activities should not generate dust emissions which result in a dust deposition rate greater than 2 g/m²/month above background levels on a annual average. Table 2-1 describes the Pollutant, Units of Measure, Monitoring Frequency and Method of Sampling.

2.1.2 Monitoring Locations

Point ID	Pollutant	Unit of measure	Frequency	Sampling Method
1	Particulates - Deposited	grams per square metre	Monthly	AM-19
(DDG1)	matter	per month		
2	Particulates - Deposited	grams per square metre	Monthly	AM-19
(DDG2)	matter	matter per month		
3	Particulates - Deposited	Particulates - Deposited grams per square metre		AM-19
(DDG3)	matter	per month		
4	Particulates - Deposited	grams per square metre	Monthly	AM-19
(DDG4)	matter	per month		
5	Particulates - Deposited	grams per square metre	Monthly	AM-19
(DDG5)	matter	per month		

Table 2-1 Endeavor Mine Air Monitoring Requirements

As shown in the satellite image (Figure 2.2), there are 5 dust monitoring locations on the boundary of the lease, with one located 11kms from the site at the turnoff to the Mine site near the Louth Road. This station was positioned to establish background levels.

For Month Ending 31 March 2021



Figure 2.2 Endeavor Mine Dust Monitoring Locations

2.1.3 Dust Monitoring Data

This report shows the results from the dust monitoring activities carried out during the month of March 2021 (Table 2-2). All values remain well under the recommended guidance values.

Monitoring locations (Monitoring from 02/03/2021 to 07/04/2021									
Parameters	Unit	DDG1	DDG2	DDG3	DDG4	DDG5			
Total soluble matterg/m2*month		*	*	*	*	*			
Total insoluble matter g/m2*mo		*	*	*	*	*			

Fable 2-2 Dust monitoring results March 2021.

* Results will be included once analysis obtained from laboratory

2.2 Groundwater Monitoring

Deep regional groundwater flows to the south west, conforming to the structural dip of the underlying sedimentary rocks. Groundwater inflow into the mine is observed at a depth range of between 60 to 80 m below ground surface. A shallow, perched aquifer occurs is found in the vicinity of the Central Tailings Discharge CTD between approximately 0.5 to 13 m below ground surface. This aquifer is recharged by rainfall and seepage water from the operational TSF via a permeable gravelly soil layer in the area.

A review of groundwater characteristics undertaken by consultants Environmental Earth Sciences (EES) in 2013 indicates there is no interface between the shallow perched water and the deep regional aquifer.

Groundwater quality at the mine is generally poor due to the high salinity. The water has been sampled by NSW Water Conservation and Irrigation for the original Environmental Impact Statement (EIS) could be considered "brackish" and was found to have an electrical conductivity (EC) of 26,000 μ S/cm (sea water is approximately 30,000 us/cm). Further, it was noted that the water was not suitable for stock, domestic or farm use. Potential contamination of the groundwater would be of low risk due to the naturally poor quality of the water.

2.2.1 Monitoring Locations

Endeavor Mine's groundwater monitoring locations are concentrated around the perimeter of the Central Tailings Discharge (CTD) and the Sector 5 Tailings Storage Facility (CTF), while surface water monitoring locations are focused on water storages that could potentially discharge to environment during a major rain or storm event. Table 2-3 describes the monitoring stations, where Figure 2.3 shows the locations of the piezometers. Depending on availability of water or flow, unfortunately on some occasions, piezometers cannot be monitored as a result of being dry. Parameters to be monitored are described in


Table 2-4.


EPA ID	Type of monitoring point	Location description
9	Groundwater monitoring point	PZ Labeled as BH02
10	Groundwater monitoring point	PZ Labeled as BH02B
11	Groundwater monitoring point	PZ Labeled as BH03
12	Groundwater monitoring point	PZ Labeled as BH06
13	Groundwater monitoring point	PZ Labeled as BH08A
14	Groundwater monitoring point	PZ Labeled as BH09
15	Groundwater monitoring point	PZ Labeled as BH10
16	Groundwater monitoring point	PZ Labeled as BH10B
17	Groundwater monitoring point	PZ Labeled as BH12B
18	Groundwater monitoring point	PZ Labeled as BH14
19	Groundwater monitoring point	PZ Labeled as BH15
20	Groundwater monitoring point	PZ Labeled as BH16
25	Groundwater monitoring point	PZ Labeled as BH13

Table 2-3 EPA Monitoring Stations

Pollutant	Unit of measure	Frequency	Sampling method
Arsenic	milligrams per litre	Quarterly	Representative sample
Cadmium	milligrams per litre	Quarterly	Representative sample
Calcium	milligrams per litre	Quarterly	Representative sample
Chloride	milligrams per litre	Quarterly	Representative sample
Copper	milligrams per litre	Quarterly	Representative sample
Cyanide (total)	milligrams per litre	Quarterly	Representative sample
Electrical conductivity	milligrams per litre	Quarterly	Representative sample
Iron	milligrams per litre	Quarterly	Representative sample
Lead	milligrams per litre	Quarterly	Representative sample
Magnesium	milligrams per litre	Quarterly	Representative sample
Manganese	milligrams per litre	Quarterly	Representative sample
Mercury	milligrams per litre	Quarterly	Representative sample
рН	рН	Quarterly	Representative sample
Potassium	milligrams per litre	Quarterly	Representative sample
Sodium	milligrams per litre	Quarterly	Representative sample
Standing water level	metres	Quarterly	Representative sample
Sulfate	milligrams per litre	Quarterly	Representative sample
Total dissolved solids	milligrams per litre	Quarterly	Representative sample
Zinc	milligrams per litre	Quarterly	Representative sample

Table 2-4 EPA Monitoring Parameters





2.2.2 Monitoring Results Data

Groundwater monitoring was carried out during the 15th and 16th of March 2021, the results are in Table 2-5.

Monthly Environmental Report

For Month Ending 31March 2021

Monitoring		s (EPA	BH 02	BH 02B	BH 03	BH 06	BH 8A	BH 9	BH 10	BH 10B	BH 12B	BH 14	BH 15	BH 16	BH 13
ID)			9	10	11	12	13	14	15	16	17	18	19	20	25
Standing W	ater Leve	els (m)	2.98	3.88	3.30	3.44	4.20	3.40	11.80	6.16	6.15	6.67	12.75	3.95	2.4
pH Value	Lab	pH Unit	7.17	7.38	7.63	6.38	7.42	7.56		7.55	7.49	7.64		6.88	7.53
Elect. Cond.	Lab	μS/cm	15000	18400	31800	13500	27200	19400		20100	26200	16600		20300	28800
Temp	Field	С	28.0	26.00	21.2	22.5	25.0	23.2		21.8	24.5	26.0		21.3	23.9
Total Diss Solids @18		mg/L	14800	15900	26800	12800	22600	21100		23800	21900	16000		17600	25700
Sulfate as	SO4 -	mg/L	6540	6850	6740	5910	6140	9700		11400	6150	7180		3430	6820
Chlorid	le	mg/L	2460	3540	8420	2400	6900	2900		2760	6600	3020		5650	7400
Calciu	m	mg/L	777	702	488	585	717	535		531	731	554		959	593
Magnesi	um	mg/L	1250	1430	1780	867	1580	1660		2290	1430	1430		723	2000
Sodiu	n	mg/L	1680	2380	4110	1410	3400	2350	*	2170	3500	1830	*	2450	2680
Potassi	um	mg/L	111	111	185	84	160	236		184	209	149		99	126
Arsen	ic	mg/L	0.169	0.065	0.006	2.56	0.002	0.008		0.006	0.006	0.009		0.002	0.005
Cadmiu	ım	mg/L	<0.0001	<0.0001	<0.0001	<0.0001	<0.0001	<0.0001		<0.0001	<0.0001	<0.0001		0.0001	<0.0001
Сорре	r	mg/L	<0.001	<0.001	0.001	<0.001	0.002	0.001		0.002	<0.001	0.001		<0.001	<0.001
Lead		mg/L	<0.001	<0.001	<0.001	<0.001	0.004	0.05		<0.001	<0.001	0.003		<0.001	<0.001
Mangan	ese	mg/L	8.61	4.45	5.85	4.69	10.8	4.07		5.34	2.89	0.028		25.0	14.6
Zinc		mg/L	0.014	0.020	0.022	0.441	0.088	0.045		0.032	0.024	0.046		0.681	0.016
Iron		mg/L	3.04	<0.05	0.65	287	<0.05	0.08		<0.05	<0.05	<0.05		25.8	2.43
Mercu	ry	mg/L	<0.0001	<0.0001	<0.0001	<0.0001	<0.0001	<0.0001		<0.0001	<0.0001	<0.0001		<0.0001	<0.0001
Total Cya	nide	mg/L	<0.004	<0.004	<0.004	<0.004	<0.004	<0.004		<0.004	<0.004	<0.004		<0.004	<0.004

 Table 2-5 Groundwater monitoring results March 2021

*Not enough water to sample

2.3 Tailings Deposition

Tailings (also known as tails or residue) are the material left over after the process of separating the valuable fraction from the uneconomic fraction (waste) of the ore. Tailings are distinct from overburden or waste rock or other material that overlies an ore or mineral body and is displaced during mining without being processed.

The volumes of tailings can be large and require an engineered storage and capacity to safely house them, Depending on the nature of the ore or the type of extraction process, tailings can have the potential to harm the environment unless they are deposited and managed correctly.

The reporting of monthly tailings deposition is a legislative requirement as part of EPL 1301.

2.3.1 Tailings Deposition: Data and Discussion

From the 1st of January 2020 the Mine has entered into Care and Maintenance, no tailings have been produced as there are no ongoing operations.

		rotection Licence ng Point 7		otection Licence ng Point 8	TOTAL
	Volume of tailings deposited (m ³)	Mass of tailing solids deposited (DMT)	Volume of tailings deposited (KL)	Mass of tailing solids deposited (DMT)	Mass of tailing solids deposited (DMT) YTD
March 2021	-	-	-	-	-

Table 2-6 Tailings Deposition for March 2021

3 RESULTS LOG

Table 3-1 Laboratory results log

Samples	Results received from laboratory
Dust deposition	Results will be included once results obtained from
	laboratory
Groundwater	26 March 2021
Date report posted on website	13 April 2021

4 COMPLAINTS HOTLINE

Endeavor Mine has established a complaints hotline for members of the Public to voice any concerns they have with Endeavor Mine activities. The phone number to call is (02) 68306555 or email on enquiries@endeavor.com.au. Endeavor will investigate any complaint and take immediate action if the complaint is validated.