

MONTHLY ENVIRONMENTAL REPORT

March 2024

Name of Operation	Endeavor Mine
Name of Licensee	Endeavor Operations Pty Ltd
Environmental Protection Licence	No: 1301
Reporting Period Start Date	1 March 2024
Reporting End Date	31 March 2024

TABLE OF CONTENTS

INTROE	DUCTION	3
2.1 Du	ıst Monitoring	3
2.1.1	Dust Monitoring Methodology and Limits	4
2.1.2	Monitoring Locations	4
2.1.3	Dust Monitoring Data	5
2.2 Gro	oundwater Monitoring	6
2.2.1	Monitoring Locations	6
2.2.2	Monitoring Results DataBookmark not d	efined.
2.3 Tai	ilings Deposition	9
2.3.1	Tailings Deposition: Data and Discussion	10
RESULT	TS LOG	10
COMPL	AINTS HOTLINE	10
	MONIT 2.1 Du 2.1.1 2.1.2 2.1.3 2.2 Gr 2.2.1 2.2.2 2.3 Ta 2.3.1 RESUL	MONITORING RESULTS 2.1 Dust Monitoring 2.1.1 Dust Monitoring Methodology and Limits 2.1.2 Monitoring Locations 2.1.3 Dust Monitoring Data 2.2 Groundwater Monitoring 2.2.1 Monitoring Locations

FIGURES LIST

Figure 2.1 Dust monitoring gauge located in the project	.3
Figure 2.2 Endeavor Mine Dust Monitoring Locations	.5
Figure 2.3 Location of the Piezometer Monitoring Locations	.8

TABLES LIST

Table 2-1 Endeavor Mine Air Monitoring Requirements	4
Table 2-2 Dust monitoring results March 2024	5
Table 2-3 EPA Monitoring Stations	6
Table 2-4 EPA Monitoring Parameters	7
Table 2-5 Groundwater Monitoring Results March 2024 Error! Bookmark not define	ed.
Table 3-1 Laboratory results log	10

1 INTRODUCTION

We at Endeavor Mine conduct systematic and periodic environmental monitoring of our operations to substantiate the effectiveness of our environmental controls which are in place to protect the environment, the health of our workers, our neighbours and the greater community. The results in this report correspond to March 2024. This report publishes the summary of the environmental monitoring carried during this month for dust deposition, tailings deposition and groundwater. All monitoring is conducted in accordance with regulatory requirements and the EOPL Annual Environmental Monitoring Plan. Samples are collected and handled in accordance and compliance with regulatory requirements and taken to laboratories accredited by the National Association of Testing Authorities (NATA) for analysis.

2 MONITORING RESULTS

2.1 Dust Monitoring

Air quality aspects and impacts associated with site operations are managed in accordance with the Air Quality Management Plan (END-PLN-ENV-006) and the requirement detailed in NSW Environmental Protection Licence 1301.

The Endeavor Mine is located 47 km from the nearest town (Cobar) and 4.5 km away for its nearest sensitive receptor (residential property). Therefore, dust deposition at these potential receptors is considered a low environmental risk.

Nevertheless, dust deposition on and beyond the boundary of the lease has the potential to cause environmental harm. Therefore Endeavor Mine manages airborne contaminants on site through the use of water sprays and a water trucks with depositional dust monitoring stations strategically located along the boundary of ML158/159/160/161 to measure performance.



Figure 2.1 Dust monitoring gauge located in the project

2.1.1 Dust Monitoring Methodology and Limits

The Endeavor Mine Dust Monitoring Program measures dust deposition rates on a monthly basis at the main mining lease boundary (4 locations) and at a background location located 11km from the operating mine site (DDG 5 – Point ID 5). EP Licence 1301 does not set limits for dust deposition. The Endeavor mine has chosen deposition rate for total insoluble matter when expressed as a 12 month rolling average should not exceed 4 g/m²/month and that site activities should not generate dust emissions which result in a dust deposition rate greater than 2 g/m²/month above background levels on a annual average. Table 2-1 describes the Pollutant, Units of Measure, Monitoring Frequency and Method of Sampling.

2.1.2 Monitoring Locations

Point ID	Pollutant	Pollutant Unit of measure I			
1	Particulates - Deposited	grams per square metre	Monthly	AM-19	
(DDG1)	matter	per month			
2	Particulates - Deposited	grams per square metre	Monthly	AM-19	
(DDG2)	matter	per month			
3	Particulates - Deposited	grams per square metre	Monthly	AM-19	
(DDG3)	matter	per month			
4	Particulates - Deposited	grams per square metre	Monthly	AM-19	
(DDG4)	matter	per month			
5	Particulates - Deposited	grams per square metre	Monthly	AM-19	
(DDG5)	matter	per month			

Table 2-1 Endeavor Mine Air Monitoring Requirements

As shown in the satellite image (Figure 2.2), there are 5 dust monitoring locations on the boundary of the lease, with one located 11kms from the site at the turnoff to the Mine site near the Louth Road. This station was positioned to establish background levels.

For Month Ending 31st March 2024



Figure 2.2 Endeavor Mine Dust Monitoring Locations

2.1.3 Dust Monitoring Data

This report shows the results from the dust monitoring activities carried out between 16/02/24 - 15/03/24 (Table 2-2). All values remain well under the recommended guidance values.

Monitoring locations (Monitoring from 15/11/2023 to 18/12/2023								
Parameters	Unit	DDG1	DDG2	DDG3	DDG4	DDG5		
Total soluble matter	g/m2*month	0.3	0.4	1.0	<0.1	0.5		
Total insoluble matter	g/m2*month	2.0	2.1	2.1	2.2	2.1		

Table 2-2 Dust monitoring results December 2023.
--

2.2 Groundwater Monitoring

Deep regional groundwater flows to the south west, conforming to the structural dip of the underlying sedimentary rocks. Groundwater inflow into the mine is observed at a depth range of between 60 to 80 m below ground surface. A shallow, perched aquifer occurs is found in the vicinity of the Central Tailings Discharge CTD between approximately 0.5 to 13 m below ground surface. This aquifer is recharged by rainfall and seepage water from the operational TSF via a permeable gravelly soil layer in the area.

A review of groundwater characteristics undertaken by consultants Environmental Earth Sciences (EES) in 2013 indicates there is no interface between the shallow perched water and the deep regional aquifer.

Groundwater quality at the mine is generally poor due to the high salinity. The water has been sampled by NSW Water Conservation and Irrigation for the original Environmental Impact Statement (EIS) could be considered "brackish" and was found to have an electrical conductivity (EC) of 26,000 μ S/cm (sea water is approximately 30,000 us/cm). Further, it was noted that the water was not suitable for stock, domestic or farm use. Potential contamination of the groundwater would be of low risk due to the naturally poor quality of the water.

2.2.1 Monitoring Locations

Endeavor Mine's groundwater monitoring locations are concentrated around the perimeter of the Central Tailings Discharge (CTD) and the Sector 5 Tailings Storage Facility (CTF), while surface water monitoring locations are focused on water storages that could potentially discharge to environment during a major rain or storm event. Table 2-3 describes the monitoring stations, where Figure 2.3 shows the locations of the piezometers. Depending on availability of water or flow, unfortunately on some occasions, piezometers cannot be monitored as a result of being dry. Parameters to be monitored are described in

Table 2-4.

EPA ID	Type of monitoring point	Location description
9	Groundwater monitoring point	PZ Labeled as BH02
10	Groundwater monitoring point	PZ Labeled as BH02B
11	Groundwater monitoring point	PZ Labeled as BH03
12	Groundwater monitoring point	PZ Labeled as BH06
13	Groundwater monitoring point	PZ Labeled as BH08A
14	Groundwater monitoring point	PZ Labeled as BH09
15	Groundwater monitoring point	PZ Labeled as BH10
16	Groundwater monitoring point	PZ Labeled as BH10B
17	Groundwater monitoring point	PZ Labeled as BH12B
18	Groundwater monitoring point	PZ Labeled as BH14
19	Groundwater monitoring point	PZ Labeled as BH15
20	Groundwater monitoring point	PZ Labeled as BH16
25	Groundwater monitoring point	PZ Labeled as BH13

Table 2-3 EPA Monitoring Stations

Pollutant	Unit of measure	Frequency	Sampling method
Arsenic	milligrams per litre	Quarterly	Representative sample
Cadmium	milligrams per litre	Quarterly	Representative sample
Calcium	milligrams per litre	Quarterly	Representative sample
Chloride	milligrams per litre	Quarterly	Representative sample
Copper	milligrams per litre	Quarterly	Representative sample
Cyanide (total)	milligrams per litre	Quarterly	Representative sample
Electrical conductivity	milligrams per litre	Quarterly	Representative sample
Iron	milligrams per litre	Quarterly	Representative sample
Lead	milligrams per litre	Quarterly	Representative sample
Magnesium	milligrams per litre	Quarterly	Representative sample
Manganese	milligrams per litre	Quarterly	Representative sample
Mercury	milligrams per litre	Quarterly	Representative sample
рН	рН	Quarterly	Representative sample
Potassium	milligrams per litre	Quarterly	Representative sample
Sodium	milligrams per litre	Quarterly	Representative sample
Standing water level	metres	Quarterly	Representative sample
Sulfate	milligrams per litre	Quarterly	Representative sample
Total dissolved solids	milligrams per litre	Quarterly	Representative sample
Zinc	milligrams per litre	Quarterly	Representative sample

Table 2-4 EPA Monitoring Parameters



Figure 2.3 Location of the Piezometer Monitoring Locations

1 TABLE 2 5 GROUNDWATER MONITORING RESULTS MARCH 2024

Monitoring Locations (EPA ID)		BH 02 9	BH 02B 10	BH 06 12	BH 08A 13	BH 09 14	BH 10 15	BH 10B 16	BH 12B 17	BH13 25	BH 14 18	BH15 19	BH 16 20	
Standing W	ater Leve	ls (m)	3.06	3.94	3.43	5.23	3.92	7.03	7.12	7.14	3.44	6.33	9.89	3.2
pH Value	Lab	pH Unit	7.32	7.36	5.46	7.39	6.97	7.76	7.64	7.39	7.43	7.66	7.63	6.51
Elect. Cond.	Lab	μS/cm	15800	27100	18900	29800	30500	26700	17100	25500	32300	16100	24300	34800
Temp	Field	С	20.60	20.65	20.90		20.80	20.84	20.85			24.10	23.20	23.18
Total Dissolve @180Â		mg/L	15600	20300	25800	24500	44000	23100	17000	18400	29100	16200	23400	28000
Sulfate as	SO4 -	mg/L	6800	4720	13400	5850	23000	8590	7600	5450	6250	6540	7640	5860
Chloric	le	mg/L	2170	7410	1780	8360	2850	5120	2350	6980	9000	2650	5280	10200
Calciu	m	mg/L	550	364	455	725	597	526	484	708	843	473	461	823
Magnesi	um	mg/L	1370	1170	2230	1440	5160	1060	1360	1270	1710	1230	1480	1310
Sodiur	n	mg/L	1770	3890	1220	4720	3130	5390	2260	3830	4910	1940	3950	5270
Potassiu	ım	mg/L	110	150	118	185	356	231	202	218	186	153	173	99
Arseni	ic	mg/L	0.314	0.042	1.68	<010	0.017	0.025	0.025	0.004	< 0.010	0.007	0.002	< 0.010
Cadmiu	ım	mg/L	<0.0001	0.0001	0.0396	<0.001 0	<0.001 0	0.0033	0.0005	<0.000 1	<0.001 0	<0.000 1	<0.000 3	0.0360
Сорре	r	mg/L	< 0.001	< 0.001	< 0.001	< 0.010	< 0.010	< 0.010	0.003	0.002	< 0.010	0.004	0.003	<0.010
Lead		mg/L	0.020	0.004	0.009	0.775	0.513	0.139	0.024	1.79	0.342	0.123	0.010	0.092
Mangan	ese	mg/L	8.62	2.47	70.0	2.48	46.3	0.159	2.78	4.83	15.1	0.510	0.294	46.1
Zinc		mg/L	0.030	0.015	78.4	0.071	0.199	1.52	1.01	0.185	0.768	0.045	0.527	94.5
Iron		mg/L	3.04	< 0.05	1970	<0.10	104	0.21	17.4	0.13	3.97	0.62	0.19	21.9
Mercui	ry	mg/L	<0.0001	<0.000 1	<0.000 1	<0.000 1	<0.000 1	<0.000 1	<0.000 1	<0.000 1	<0.000 1	<0.000 1	<0.000 5	<0.000 1
Total Cya	nide	mg/L	<0.004	<0.004	<0.006	<0.004	<0.004	<0.004	<0.004	<0.004	<0.004	<0.004	<0.004	<0.004

ENDEAVOR OPERATIONS PTYLTD

9 | P a g e

2.3 Tailings Deposition

Tailings (also known as tails or residue) are the material left over after the process of separating the valuable fraction from the uneconomic fraction (waste) of the ore. Tailings are distinct from overburden or waste rock or other material that overlies an ore or mineral body and is displaced during mining without being processed.

The volumes of tailings can be large and require an engineered storage and capacity to safely house them, Depending on the nature of the ore or the type of extraction process, tailings can have the potential to harm the environment unless they are deposited and managed correctly.

The reporting of monthly tailings deposition is a legislative requirement as part of EPL 1301.

2.3.1 Tailings Deposition: Data and Discussion

From the 1st of January 2020 the Mine has entered into Care and Maintenance, no tailings have been produced as there are no ongoing operations.

		rotection Licence ng Point 7		rotection Licence ng Point 8	TOTAL
	Volume of tailings deposited (m ³)	Mass of tailing solids deposited (DMT)	Volume of tailings deposited (KL)	Mass of tailing solids deposited (DMT)	Mass of tailing solids deposited (DMT) YTD
Mar 2024	-	-	-	-	-

Table 2-6 Tailings Deposition for Mar 2024

3 RESULTS LOG

Table 3-1 Laboratory results log

Samples	Results received from laboratory
Dust deposition	Mar 2024
Groundwater	Mar 2024
Date report posted on website	ТВА

4 COMPLAINTS HOTLINE

Endeavor Mine has established a complaints hotline for members of the Public to voice any concerns they have with Endeavor Mine activities. The phone number to call is (02) 68306555 or email on enquiries@endeavor.com.au. Endeavor will investigate any complaint and take immediate action if the complaint is validated.